



EMCON TEMPEST Level I Version Cisco's IP Phone 7960G

EMCON introduces a TEMPEST version of Cisco's IP Phone 7960G for government users requiring full TEMPEST computing environments.

This phone meets the requirements of: NSTISSAM TEMPEST/1-92, Level I; CID09/15A, Level I; and SDIP-27 Level A (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).

Primarily designed for manager and executive needs, this phone addresses high or busy telephone traffic and offers display-based access to features, productivity-enhancing applications and valued-added services.

Cisco's IP Phone 7960G features:

- Built-in headset connection
- Six lines – mix directory numbers or speed dial, call waiting
- Display area: pixel display with dynamic feature access using “soft keys”
- Additional display area for value-added services and applications
- Info key for “on-line” help with features
- Visual Message Waiting Indicator
- Multi-protocol support -SCCP, SIP and MGCP
- Services key for XML-based information
- 24 user-selectable ringers
- 100Base-FX-ST fast Ethernet connection

Specifications

- Download firmware changes from Cisco CallManager and CCO
- ABS/aluminum in a textured dark grey color with silver bezel

Power	100-240 VAC .05A 50-60 HZ UL/CSA approved
--------------	--

Environmental Ranges

Operating Temp.	0°C to 40°C (32°F to 104°F)
Storage Temp.	-10°C to 60°C (14°F to 140°F)
Relative Humidity	10 to 95% (noncondensing)

Physical Characteristics

Height	20.32 cm (8.2 in.)
Width	26.67 cm (10.5 in.)
Depth	15.24 cm (6.0 in.)
Weight	2.73 kg (6.0 lbs.)

Warranty

One-year, parts and labour, return to depot

EMCON Emanation Control Limited
11 Tristan Court, Nepean, Ontario, Canada K2E 8B9
Tel: (613) 723-1838 Fax: (613) 723-2752
e-mail: sales@emcon.com Web Site: www.emcon.com