



EMCON Version HP LaserJet P3005 Printers

EMCON has developed a series of workgroup black and white laser printers for government users. These printers are available in the following choices:

- TEMPEST Level I - This printer meets the requirements of: NSTISSAM TEMPEST/1-92, Level I; CID09/15A, Level I; and SDIP-27 Level A (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).
- TEMPEST Level II - This printer meets the requirements of NSTISSAM TEMPEST/1-92 Level II; CID09/15A, Level II; and SDIP-27 Level B (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).
- Zone.

This high-quality, reliable, laser printer prints at 35 pages per minute and gets the first page out quickly with Instant-on Technology. The P3005 has an optional 500-sheet tray for a total input capacity of 1,100 sheets.

Specifications

Technology	Laser
Processor	400 MHz
Resolution	1200 x 1200 dpi; HP FastRes 1200
Speed	35 pages per minute, letter
Memory	
Standard	48 MB RAM
Optional	Upgradeable to 320 MB through one industry standard 144-pin DIMM slot; Memory Enhancement Technology
Connectivity	
Standard	IEEE 1284 compliant parallel port, High speed USB 2.0 port, one open EIO slot
Optional	100FX-SC print server

Paper Handling

Standard	100-sheet multipurpose tray 500-sheet automatic feed tray
Optional	Second 500-sheet automatic feed tray Automatic duplex printing

Media

Sizes	Letter, legal, executive, 8.5 x 14 in., envelopes
Types	Paper (plain, preprinted, letterhead, prepunched, bond, recycled, color, rough) transparencies, labels, envelopes, card stock, user-defined

Print Languages

Standard	HP PCL 6, HP PCL 5e and HP Postscript® level 3 emulation
----------	--

Font Capabilities

PCL Standard	103 internal font set
--------------	-----------------------

Power	100-127 V	50/60 Hz
	220-240 V	50/60 Hz
Must be specified at time of order.		

Environment

Temperature	15°C to 32.5°C (59°F to 89°F)
Humidity	Recommended: 30 to 70% RH; non-operating: 10 to 90%

Physical Specifications

Height	30.9 cm (12.2 in.)
Width	42.5 cm (16.7 in.)
Depth	41.0 cm (16.1 in.)
Weight	16.2 kg (35.7 lb.)

Warranty

One-year, parts and labour, return to depot

EMCON Emanation Control Limited
 11 Tristan Court, Nepean, Ontario, Canada K2E 8B9
 Tel: (613) 723-1838 Fax: (613) 723-2752
 e-mail: sales@emcon.com Web Site: www.emcon.com