



## EMCON Black and White – HP LaserJet P3015dn Printers

EMCON has developed a series of workgroup black and white laser printers for government users. These printers are available in the following choices:

- **TEMPEST Level I** - This printer meets the requirements of: NSTISSAM TEMPEST/1-92, Level I; CID09/15A, Level I; and SDIP-27 Level A (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).
- **TEMPEST Level II** - This printer meets the requirements of NSTISSAM TEMPEST/1-92 Level II; CID09/15A, Level II; and SDIP-27 Level B (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).
- **Zone.**

This high-quality, reliable, laser printer prints at 42 pages per minute and gets the first page out quickly with Instant-on Technology.

---

### Specifications

<b>Technology</b>	Laser
<b>Processor</b>	540 MHz
<b>Resolution</b>	1200 x 1200 dpi; HP FastRes 1200
<b>Speed</b>	Up to 42 pages per minute, letter
<b>Memory</b>	
Standard	128 MB RAM
Optional	Upgradeable to 640 MB
<b>Connectivity</b>	
Standard	High speed USB 2.0 port
Optional	100FX-SC fibre port 100FX-ST fibre port

---



---

### Paper Handling

<b>Standard</b>	100-sheet multipurpose tray 500-sheet automatic feed tray
<b>Optional</b>	Additional 500-sheet tray

---

### Media

<b>Sizes</b>	Letter, legal, executive, 8.5 x 14 in., envelopes
<b>Types</b>	Paper (plain, preprinted, letterhead, prepunched, bond, recycled, color, rough) transparencies, labels, envelopes, card stock, user-defined

---

### Print Languages

<b>Standard</b>	HP PCL 6, HP PCL 5e and HP Postscript® level 3 emulation
-----------------	--

---

### Font Capabilities

<b>PCL Standard</b>	103 internal font set
---------------------	-----------------------

<b>Power</b>	100-127 V      50/60 Hz 220-240 V      50/60 Hz Must be specified at time of order.
--------------	---

---

### Environment (Recommended)

<b>Temperature</b>	15°C to 32.5°C (59°F to 89°F)
<b>Humidity</b>	Recommended: 30 to 70% RH; non-operating: 10 to 90%

---

### Physical Specifications

<b>Height</b>	31.5 cm (12.4 in.)
<b>Width</b>	44.7 cm (17.6 in.)
<b>Depth</b>	41.1 cm (16.2 in.)

---

### Warranty

One-year, parts and labour, return to depot

---

**EMCON Emanation Control Limited**  
**360 Terry Fox Drive, Ottawa, Ontario, Canada, K2K 2P5.**  
**Tel: (613) 270-9009 Fax: (613) 270-0095**  
**Email: sales@emcon.com Web Site: www.emcon.com**