



TEMPEST Level I Scanner

Based on the Fujitsu™ fi-5530C2 High Speed Colour Duplex Scanner

This product meets the requirements of: NSTISSAM TEMPEST/1-92, Level I; CID09/15A, Level I; and SDIP-27 Level A (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).

Features

- 100 page automatic document feeder
- Ultrasonic multi-feed detection
- Auto colour detection, blank page deletion, auto cropping, auto de-skew

Technical Specifications

Scanning speed

50 pages/100 images per minute (landscape, 200 dpi)

35 pages/70 images per minute (portrait, 200 dpi)

Scanning range

Minimum 2.0" x 2.9" (52 x 74 mm)

Maximum 11" x 34" (297 x 863 mm)

Paper chute capacity

Max. 100 sheets (8.5"x11")

Max. 50 sheets (11"x17")

Optical resolution

50 to 600 dpi

Scanning modes

Simplex / Duplex Colour / Greyscale / Monochrome

Output format

24 bit (colour), 8 bit (greyscale), or 1 bit (monochrome).

Interface

USB 2.0 (TEMPEST cable included)

Voltage

AC 100 to 240 V, 50/60 Hz

Power

Operating 57 watts or less

Sleep mode Less than 7.5 watts

Physical

Dimensions (W x D x H)

399 mm x 225 mm x 193 mm (15.7" x 8.8" x 7.5")

8.6 kg (19.0 lbs)

Operational environment

Temperature 5°C to 35°C (42°F to 95°F) Relative humidity

20% to 80% (non-condensing)

Warranty

One year, parts and labour, return to depot

Optional

Post-scanning imprinter

Prints numbers, letters and codes on original document after they have been scanned.

EMCON Emanation Control Limited
11 Tristan Court, Nepean, Ontario, Canada K2E 8B9
Tel: (613) 723-1838 Fax: (613) 723-2752
e-mail: sales@emcon.com Web Site: www.emcon.com