



TEMPEST High Volume Scanner

Based on the Fujitsu™ fi-5900C High-Volume Production Scanner

This product meets the requirements of: NISTISSAM TEMPEST/1-92, Level I; CID09/15A, Level I; and SDIP-27 Level A (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).

Features

- 500 page automatic document feeder
- Ultrasonic multi-feed detection
- Auto colour detection, blank page deletion, auto cropping, auto de-skew



Technical Specifications

Scanning speed

Up to 120 pages/240 images per minute

Scanning range

Minimum 2.0" x 3.0" (52 x 75 mm)

Maximum 12" x 34" (299 x 863 mm)

Paper chute capacity

500 sheets

Optical resolution

50 to 600 dpi

Output format

Colour: 24 bit, Greyscale: 8 bit, Monochrome: 1 bit

Interface

USB 2.0 (TEMPEST cable included)

Voltage

AC 100 to 240V, (+10% / -10%)

Power

Operating 250 watts or less

Sleep mode Less than 12 watts

Physical

Dimensions (W x D x H)

540 mm x 540 mm x 500 mm (21.3" x 21.3" x 19.7")

50 kg (110 lb.)

Operational environment

Temperature 15°C to 35°C (59°F to 95°F)

Relative humidity 20% to 80% (non-condensing)

Warranty

One year, parts and labour, return to depot

Optional

Pre-scanning imprinter

Prints information on the front of documents prior to scanning

Post-scanning imprinter

Prints information of the back of the original documents after they have been scanned

EMCON Emanation Control Limited
11 Tristan Court, Nepean, Ontario, Canada K2E 8B9
Tel: (613) 723-1838 Fax: (613) 723-2752
e-mail: sales@emcon.com Web Site: www.emcon.com